

**AMENDMENTS TO THE CLAIMS**

1. (currently amended) An illegal access data handling apparatus, being comprising:  
a control system; and  
a decoy server, functionally coupled to the control system, wherein the apparatus is  
placed outside a given internal communication network, for receiving illegal access data  
transmitted from a data communication device placed outside the internal communication  
network for a purpose of illegally accessing the internal communication network, and for taking  
countermeasures against the illegal access data received, further wherein the countermeasures  
include providing a response pretending to originate from the internal communication network.

2. (previously presented) The illegal access data handling apparatus of claim 1, wherein the  
illegal access data handling apparatus is connected to an illegal access data detection device for  
relaying a data communication between a data communication device placed within the internal  
communication network and a data communication device placed outside the internal  
communication network, and for detecting the illegal access data, and

wherein the illegal access data handling apparatus receives the illegal access data from  
the illegal access data detection device.

3. (currently amended) The illegal access data handling apparatus of claim 2, further comprising:  
a data reception section for receiving the illegal access data from the illegal access data  
detection device;

a data analysis section for analyzing the illegal access data received by the data reception

section;

a response data generation section for generating response data to the illegal access data based upon an analysis result from the data analysis section; and

a data transmission section for transmitting the response data generated by the response data generation section to the illegal access data detection device.

4. (previously presented) The illegal access data handling apparatus of claim 3, wherein the data reception section receives an encapsulated illegal access data from the illegal access data detection device,

wherein the illegal access data handling apparatus further includes a capsulation section for decapsulating the encapsulated illegal access data received by the data reception section to extract the illegal access data, and encapsulates the response data, and

wherein the data transmission section transmits the response data encapsulated by the capsulation section to the illegal access data detection device.

5. (original) The illegal access data handling apparatus of claim 3, wherein the response data generation section generates response data having same contents as those of response data that would be generated by a specific data communication device placed in the internal communication network in response to the illegal access data if the specific data communication device received the illegal access data.

6. (original) The illegal access data handling apparatus of claim 3, wherein the data reception

section receives from the illegal access data detection device communication history information indicating a communication history of the illegal access data detection device,

wherein the data analysis section analyzes the communication history information received by the data reception section, and generates illegal access data designation information designating data transmitted from a given data communication device placed outside the internal communication network as the illegal access data based upon an analysis result of the communication history information, and

wherein the data transmission section transmits the illegal access data designation information generated by the data analysis section to the illegal data detection device.

7. (original) The illegal access data handling apparatus of claim 4, wherein the data reception section receives the illegal access data having authentication information attached to be used for data authentication from the illegal access data detection device, and

wherein the capsulation section performs the data authentication for the illegal access data by using the authentication information.

8. (original) The illegal access data handling apparatus of claim 7, wherein the capsulation section attaches the authentication information to be used for the data authentication for the response data to the response data, and

wherein the data transmission section transmits the response data having the authentication information attached by the capsulation section to the illegal access data detection device.

9. (currently amended) A method for handling illegal access data outside a given internal communication network, the method comprising:

receiving illegal access data transmitted from a data communication device placed outside the internal communication network for a purpose of illegally accessing the internal communication network; and

taking countermeasures against the illegal access data received, wherein the countermeasures include providing a response pretending to originate from the internal communication network.

10. (previously presented) The method of claim 9, comprising:

communicating with an illegal access data detection device for relaying a data communication between a data communication device placed within the internal communication network and a data communication device placed outside the internal communication network, and for detecting the illegal access data; and

receiving the illegal access data from the illegal access data detection device.

11. (original) The method of claim 10, comprising:

receiving the illegal access data from the illegal access data detection device;

analyzing the illegal access data received by the receiving;

generating response data to the illegal access data based upon an analysis result from the analyzing; and

transmitting the response data generated by the generating to the illegal access data

detection device.

12. (original) The method of claim 10, generates response data having same contents as those of response data that would be generated by a specific data communication device placed in the internal communication network in response to the illegal access data if the specific data communication device received the illegal access data.

13. (currently amended) A method for responding to unauthorized access to an internal communications network, comprising:

receiving an encapsulated unauthorized access packet at a data center placed outside the internal network, and wherein the unauthorized access packet is redirected from a target server residing within the internal network;

analyzing the received packet to formulate a response packet;

encapsulating the response packet so that it appears to originate from the target server;

and

sending the encapsulated response packet to [[the]] a network device, wherein the network device is within the internal network.

14. (previously presented) The method according to claim 13, further comprising:

determining if the encapsulated unauthorized access packet was transmitted from a client;

judging whether data of the encapsulated unauthorized access packet came from an unauthorized source;

analyzing the encapsulated unauthorized access packet based upon data from a knowledge base; and

notifying a decoy server of the analysis result.

15. (previously presented) The method according to claim 14, further comprising:

referring to a client database; and

collating the encapsulated unauthorized access packet with information contained in the client database.

16. (previously presented) The method according to claim 14, further comprising:

accessing a knowledge base having information associated with past encapsulated unauthorized access packets.

17. (previously presented) The method according to claim 13, wherein the network device decapsulates the encapsulated response packet and forwards the decapsulated packet to the source of the unauthorized access packet.